

IN THE CLAIMS:

Claims 1-6 (Canceled)

7. (Previously Presented) A flow control comprising:

(A) a conduit including an inlet, an outlet, and an outer peripheral surface, a gas inlet passage being formed in said conduit and being configured to permit a gas to enter said conduit between said inlet and said outlet; and

(B) a flow control washer that is disposed in said conduit between said inlet and said outlet, said flow control washer being configured to maintain a generally constant volumetric liquid flow rate through said flow control despite pressure fluctuations at said inlet of said conduit, wherein said gas inlet passage opens into a low pressure region of said conduit located between said flow control washer and said outlet,

wherein said low pressure region comprises a venturi, said venturi including a throat, an inlet portion that is located upstream of said throat and that tapers inwardly toward said throat, and an outlet portion that is located downstream of said throat and that tapers outwardly away from said throat, and wherein said gas inlet passage opens into said venturi downstream of said inlet portion,

wherein said venturi is formed in said conduit, and

wherein said conduit is formed from two interconnected sections, and wherein said flow control washer is positioned between said sections.

8. (Previously Presented) A flow control comprising:

(A) a conduit including an inlet, an outlet, and an outer peripheral surface, a gas inlet passage being formed in said conduit and being configured to permit a gas to enter said conduit between said inlet and said outlet; and

(B) a flow control washer that is disposed in said conduit between said inlet and said outlet, said flow control washer being configured to maintain a generally constant volumetric liquid flow rate through said flow control despite pressure fluctuations at said inlet of said conduit,

wherein said gas inlet passage opens into a low pressure region of said conduit located between said flow control washer and said outlet,

wherein said low pressure region comprises a venturi, said venturi including a throat, an inlet portion that is located upstream of said throat and that tapers inwardly toward said throat, and an outlet portion that is located downstream of said throat and that tapers outwardly away from said throat, and wherein said gas inlet passage opens into said venturi downstream of said inlet portion, and

wherein said venturi is formed in an insert that forms at least part of said conduit and that is mounted in a fitting, and wherein said gas inlet passage is formed from a bore in said insert, a passage between said insert and said fitting, and a bore in said fitting that opens to the ambient atmosphere.

9. (Currently Amended) ~~A flow control of claim 1~~ A flow control comprising:

(A) a conduit including an inlet, an outlet, and an outer peripheral surface, a gas inlet passage being formed in said conduit and terminating in a gas inlet that is configured to permit a gas to flow into said gas inlet passage and enter said conduit between said inlet and said outlet; and

(B) a flow control washer that is disposed in said conduit between said inlet and said outlet, said flow control washer being configured to maintain a generally constant volumetric liquid flow rate through said flow control despite pressure fluctuations at said inlet of said conduit, wherein entrance of the gas attenuates noise generation that would otherwise occur through operation of said flow control washer, wherein said gas inlet passage includes a bore having a diameter of between 0.020" and 0.060".

10. (Original) A flow control of claim 9, wherein said bore has a diameter of about 0.035".

11. (Currently Amended) ~~A flow control of claim 1~~ A flow control comprising:

(A) a conduit including an inlet, an outlet, and an outer peripheral surface, a gas inlet passage being formed in said conduit and terminating in a gas inlet that is

configured to permit a gas to flow into said gas inlet passage and enter said conduit between said inlet and said outlet;

(B) a flow control washer that is disposed in said conduit between said inlet and said outlet, said flow control washer being configured to maintain a generally constant volumetric liquid flow rate through said flow control despite pressure fluctuations at said inlet of said conduit, wherein entrance of the gas attenuates noise generation that would otherwise occur through operation of said flow control washer; and

(C) ~~further comprising~~ a one-way valve that is disposed in said gas inlet passage.

12. (Previously Presented) A flow control comprising:

(A) a conduit including an inlet, an outlet, and an outer peripheral surface, a gas inlet passage being formed in said conduit and being configured to permit a gas to enter said conduit between said inlet and said outlet;

(B) a flow control washer that is disposed in said conduit between said inlet and said outlet, said flow control washer being configured to maintain a generally constant volumetric liquid flow rate through said flow control despite pressure fluctuations at said inlet of said conduit; and

(C) a one-way valve that is disposed in said gas inlet passage, wherein the one-way valve comprises a duck-billed valve.

13. (Previously Presented) A flow control comprising:

(A) a conduit including an inlet, an outlet, and an outer peripheral surface, wherein a venturi is disposed in said conduit between said inlet and said outlet, said venturi including a throat, an inlet portion that is located upstream of said throat and that tapers inwardly toward said throat, and an outlet portion that is located downstream of said throat and tapers outwardly away from said throat, and wherein an ambient air inlet passage is formed in said conduit and terminates in an ambient air inlet that is configured to permit ambient air to flow into said ambient air inlet passage and enter said venturi downstream of said inlet portion; and

(B) a flow control washer that is disposed in said conduit between said inlet and said venturi, said flow control washer being configured to maintain a generally constant volumetric liquid fluid flow rate therethrough despite pressure fluctuations at said inlet of said conduit, wherein entrance of the ambient air attenuates noise generation that would otherwise occur through operation of said flow control washer.

14. (Original) A control valve comprising:

(A) a service port configured for connection to a resin tank containing a treatment medium;

(B) an inlet port configured for connection to a source of untreated water;

- (C) a treated water outlet port;
- (D) a wastewater drain port; and
- (E) a flow control coupled to said wastewater drain port, said flow control including

- (1) conduit including an inlet, an outlet, and an outer peripheral surface, wherein a venturi is disposed in said conduit between said inlet and said outlet, said venturi including a throat, an inlet portion that is located upstream of said throat and that tapers inwardly toward said throat, and an outlet portion that is located downstream of said throat and that tapers outwardly away from said throat, and wherein an ambient air inlet passage is formed in said conduit and is configured to permit ambient air to enter said venturi downstream of said inlet portion from a location external of said water softener control valve;

- (2) a one way valve disposed in said ambient air inlet passage; and

- (3) a flow control washer that is disposed in said body between said inlet and said venturi, said flow control washer being configured to maintain a generally constant fluid volumetric liquid flow rate therethrough despite pressure fluctuations at said inlet.

15. (Original) A water softener comprising:

- (A) a brine tank;

- (B) a resin tank contain a treatment medium; and
- (C) a water softener control valve including
  - (1) a brine port fluidically coupled to said brine tank;
  - (2) a service port fluidically coupled to said resin tank; and
  - (3) an inlet port configured for connection to a source of untreated water;
  - (4) a treated water outlet port;
  - (5) a wastewater drain port; and
  - (6) a flow control coupled to said wastewater drain port, said flow control including
    - (a) a conduit including an inlet, an outlet, and an outer peripheral surface, wherein a venturi is disposed in said conduit between said inlet and said outlet, said venturi including a throat, an inlet portion that is located upstream of said throat and that tapers inwardly toward said throat, and an outlet portion that is located downstream of said throat and that tapers outwardly away from said throat, and wherein an ambient air inlet passage is formed in said conduit and is configured to permit ambient air to enter said venturi downstream of said inlet portion from a location external of said water softener control valve;

(b) a one way valve disposed in said ambient air inlet passage;  
and

(c) a flow control washer that is disposed in said body between  
said inlet and said venturi, said flow control washer being configured to  
maintain a generally constant volumetric liquid flow rate therethrough  
despite pressure fluctuations at said inlet.

16. (Original) A method of controlling flow of a liquid through a conduit comprising:

(A) directing the liquid to flow through said conduit at an initial supply  
pressure that fluctuates;

(B) directing the liquid through an aperture in a flow control washer  
located within said conduit, said aperture varying in size with fluctuations in supply  
pressure so as to maintain an at least generally constant volumetric liquid flow rate  
through said aperture; and

(C) attenuating noise generation that would otherwise occur through  
operation of said flow control washer by admitting a gas into said conduit.

17. (Original) A method of claim 16, wherein the noise attenuation step comprises  
admitting ambient air into a low pressure region of said conduit located downstream of  
said flow control washer.



18. (Original) A method of claim 17, wherein said low pressure region comprises a venturi having a throat, an inlet portion that is located upstream of said throat and that tapers inwardly toward said throat, and an outlet portion that is located downstream of said throat and that tapers outwardly away from said throat, and wherein the noise attenuation step comprises admitting ambient air into said venturi at a location downstream of said inlet portion.

19. (Original) A method of claim 16, wherein the noise attenuation step comprises admitting ambient air into an ambient air inlet passage opening into said conduit, and further comprising preventing liquid flow out of said ambient air inlet passage via operation of a one-way valve disposed in said ambient air inlet passage.

20. (Original) A method of claim 16, wherein the noise attenuation step comprises reducing noise levels by at least 5 decibels when compared to noises that would be generated by flow of the same liquid through said orifice at the same average supply pressure and the same volumetric flow rate.

21. (Original) A method of claim 16, wherein the step (A) comprises directing liquid through said conduit at a volumetric flow rate of between 0.5 gpm and 25 gpm.

22. (Original) A method of claim 16, wherein the step (A) comprises directing liquid into said conduit at an average supply pressure of between 20 psi and 125 psi.

Claims 23-27 (Canceled)

28. (Currently Amended) ~~A flow control of claim 27,~~ A flow control comprising:

(A) a conduit including an inlet and an outlet;

(B) a flow control washer that is disposed in said conduit between said inlet and said outlet, said flow control washer being configured to maintain a generally constant volumetric liquid flow rate through said flow control despite pressure fluctuations at said inlet of said conduit; and

(C) means, communicating with said conduit, for attenuating noise generation that would otherwise occur through operation of said flow control washer by admitting a gas into said conduit,

wherein the means for attenuating noise generation comprises a gas inlet passage opening into said conduit and configured to permit a gas to enter said conduit between said inlet and said outlet,

wherein said gas inlet passage opens into a low pressure region of said conduit located between said flow control washer and said outlet, and

wherein said low pressure region comprises a venturi, said venturi including a throat, an inlet portion that is located upstream of said throat and that tapers inwardly toward said throat, and an outlet portion that is located downstream of said throat and that tapers outwardly away from said throat, and wherein said gas inlet passage opens into said venturi downstream of said inlet portion.

29. (Previously Presented) A flow control of claim 28, wherein said gas inlet passage opens into said throat.

30. (Previously Presented) A flow control of claim 28, wherein said gas inlet passage opens into said downstream portion of said venturi.